



Alubond[®] Canada Color Chart

Alubond[®] The Worlds Largest ACP Brand




Production
25,000,000 M²
Capacity

Countries
100
Distributed

Installed
100,000,000 M²
Worldwide

Over
2
Decades




Alubond has been the face of iconic projects Worldwide extensively specified by World Renowned Architects as their choice for exterior facades and interior ceilings and wall linings. the tallest tower in the world Burj Khalifa by Skidmore, Owings and Merrill (SOM), The Address Hotel by W.S Atkins, The Formula One Yas Island by Burt Hill, Index Tower by Sir Norman Foster, Infosys Training Center by Hafiz Contractor, International Airports of Dubai, Sharjah, Hyderabad, Mumbai, Cairo, Sharm Al Sheik, Khartoum by Dar al Handasah and other International Architects are some of the selected project references



Alubond's array of colors and finishes combined with the inherent capability of forming different shapes and contours with durability and weather resistance makes Alubond an Architects Dream. Major Corporations and Multi National Companies have a definitive desire to make their structures an expression of Personal Designer Statement. Alubond becomes a natural choice to achieve this objective. The possible applications are limited to the architects imagination. The versatility of Alubond Metal Composite Panels allow the product to have conventional as well as Exotic Applications.



OUR RANGE OF METAL SKIN :



ACCORDING TO REACTION TO FIRE CLASS

FR - A1 - EN 13501 - 1 - CLASS A1

FR - A2 - EN 13501 - 1 - CLASS A2

FR - B2 - EN 13501 - 1 - CLASS E

- DIN4102 - 1 - CLASS B2


- NFPA 259 Meet The Requirements

FR - EUROCLASS B - EN 13501 - 1 - CLASS B

- ASTM E84 - CLASS A - CORE EXPOSED

- NFPA 285 Meet The Requirements

Alubond Total Solutions concept is designed to offer a complete Turnkey package of engineering, supply and installation of Alubond Fire Rated Metal Composites / Alubond Solid Aluminium panels using an open joint silicon free ventilated substructure system with a full system warranty of 10 years



The Total Solutions concept includes services from facade engineering onsite building survey, engineering drawings of project specific fixing details, structural analysis of full system of panels with ABTI substructure, fabrication of panels and substructure, supply of full system including accessories to site, installation services by approved installers, Alubond approval of installed system and release of 10 years warranty for the full system.



ALM 101 - BRIGHT SILVER



ALM 102 - CHAMPAGNE GOLD



ALM 103 - METALLIC BRASS



ALM 104 - GRAY METALLIC SILVER



ALM 106 - METALLIC JADE



ALM 107 - CHAMPAGNE SILVER



ALM 108 - METALLIC BRONZE




ALM 109 - METALLIC GOLD



ALM 110 - BRUSHED SILVER



ALM 112 - DESERT ROSE METALLIC



ALM 113 - BLUE METALLIC



ALM 115 - BRIGHT CHAMPAGNE SILVER



ALM 121 - RAW GREY



ALM 133 - SMOKE SILVER



ALM 143 - METALLIC BLACK



ALS-117 YELLOW



ALS 118 - SIGNAL RED



ALS 119 - SEA BLUE



ALS - 120 DARK BLUE



ALS 122 - RAT GREY



ALS 125 - WHITE




ALS 126 - APRICOT WHITE



ALS 127 - IVORY WHITE



ALS 128 - PURE WHITE




ALS 130 - COAL BLACK



ALS 137 - BURGUNDY



ALS 140 - BONE WHITE



ALS 142 - PURPLE BLUE



ALS 377 - ORANGE



ALS 430 - CREAM WHITE



ALW 314 - WHITE AHRON



ALW 321 - ORIENTAL CANE



ALW 322 - NATURAL OAK



ALW 301 - WALNUT



ALW 316 - ROSEWOOD



ALW 323 - ROYAL TEAK



ALW 320 - TEAK



ALW 319 - DARK TEAK



ALW 317 QUERCUS



ALW 315 - WENGE



ALW 309 - ROYAL WENGE



ALW 304 - MAHOGANY



ALG 212 - WHITE GRANITE



ALG 214 - YELLOW GRANITE



ALG 201 - ROSA PORRINHO



ALG 211 - ROSA GRANITE



ALG 208 - SERPEGIANTE



ALG 202 - GRANITE NERO



ALG 215 - WHITE MARBLE



ALG 206 - TRAVERTINE




ALG 216 - YELLOW MARBLE



ALG 203 - CAFFEE MARNO



ALP 401 - PRISMATIC VIOLET



ALP 402 - PRISMATIC WHITE




ALP 404 - PRISMATIC GREY




ALP 405 - PRISMATIC OLIVE



ALK 501 - SPARKLING BLACK



ALK 502 - SPARKLING WHITE



ALK 504 - SPARKLING GOLD



ALK 505 - SPARKLING GREY



ALM 801 - BRUSH



ALM 802 - TI - LOOK




ALM 900 - GOLD 20



ALM 902 - BRONZE 60



ALM 903 BRONZE 40



ALM 905 - BRONZE 55



ALR 601 - HIGH MIRROR



ALS 447 - GOLD MIRROR

Interior



ALS 340 - SOLAR SILVER MIRROR



ALS 362 SOLAR GOLD MIRROR

Exterior



ALM 101 - BRIGHT SILVER



ALM 107 - CHAMPAGNE SILVER



ALM 121 - RAW GREY




ALM 143 - METALLIC BLACK



ALS 118 - SIGNAL RED



ALS 128 - WHITE



ALS 130 - COAL BLACK

PANEL DIMENSIONS


STANDARD WIDTH	1250mm
AVAILABLE WIDTH	1000 mm, 1500mm, 1800 mm
STANDARD LENGTH	3200 mm, 4000 mm
AVAILABLE LENGTH	Custom order upto 11000 mm
AVAILABLE THICKNESS	3mm , 4mm , 5mm, 6mm
AVAILABLE SKIN THICKNES	0.3mm - 0.5mm

* Note : FR A2 Max Width 1500 mm

PANEL TOLERANCE

LENGTH	+ 4 mm
WIDTH	+ 2 mm
THICKNESS	+ 0.2 mm upto 4 mm, + 0.3 mm upto 6 mm
BOW (LENGTH AND OR WIDTH)	Maximum 0.8%
SQUARENESS	Maximum 5 mm
SKIN THICKNESS	As per International Standards

PRODUCT COMPOSITES




PRODUCT ADVANTAGES

- **LIGHTWEIGHT**, yet extremely rigid and flat resulting in an economical option for high quality building facades and interior cladding.
- **WEATHER RESISTANCE** combined with high acoustics, Thermal and Fire rated values.
- **EXTENSIVE CHOICE** of finishes including Solid, Metallic, Granite, Veneer, and Chameleon Colors.
- **HIGHLY MALLEABLE** gives flexibility of shapes making it a versatile panel to achieve complex design solutions.



ALUBOND is a metal composite panel consisting of two layers of a metallic or LDPE skin like aluminium, stainless steel, copper, zinc, titanium etc. sandwiching a fire rated core in a continuous co-extrusion process.

CORE SELECTION



Alubond has emerged as The Worlds Largest ACP Brand with new expansions under process in U.S.A, Russia, Saudi Arabia and Sri Lanka. The annual global production capacity is over 25 million m2

SURFACE FINISH :

Alubond Composite sheets are available in PVDF/ Lumiflon / HDPE Paint systems and can be supplied in any of the paint system as per the requirement of the customers.

Alubond maintains consistent coating quality through the application of the paints to the Aluminium coil on a continuous coil coating line. Alubond composite sheets are available in Solid Colors, Metallic Colors, Natural Stone & Timber Colors, Prismatic and Sparkling Colors.

WOOD & STONE SERIES :

Alubond Wood and Stone series composite sheets are developed with state of the art coating technology and with special image transfer process. This coating technology provides excellent natural feel to the surface of the wood/stone series products with outstanding quality.

LONGER DURABILITY :

Alubond anodized series, which are manufactures with the new generation Eloxal coating process provides a longer durability in exterior environment with its high resistance to all weather conditions and offers a Total Solution to customers.

IMAGINATION :

Alubond Composite sheets offer wide range of colors, choice of surface finishes, products with special patterns and exotic metals which can be used for both interior and exterior environments leaving no limits for imagination for the customers.

OUR PROMISE OF QUALITY:

Alubond is a global brand for the architectural projects and preferred by architects and consultants due to the excellent performance and durability in any kind of weather condition. Development of innovative product range with highest quality and at most competitive prices provide Alubond the edge over other brands and position Alubond as the leader in the Industry

DRILLING :



The Drilling of Alubond ACP panels can be achieved with twist drills normally used for aluminum and plastics on machines common for metals.

By using high-speed, low feed, occasional raising of the drill and blowing with compressed air, swarf will be rapidly removed

WELDING :



The Alubond ACP panels can be successfully welded using polyethylene welding rods and a hot air gun. Slender pieces of Alubond acp panels can also be used on a welding rod. Reinforcement on the welded joint is recommended.

CUTTING & SAWING :



A fine tooth tungsten - carbide tipped (CT) saw blade is the most suitable for cutting Alubond ACP panel. Eg A 60 tooth on 250 mm diameter.

CURVING / FOLDING :




Using the standard 3004 H14 / H16 alloy. Alubond can be curved to the following minimum radii :

Panel Thickness 3mm 4mm and 6mm Radius 120 mm 175 mm and 275 mm
Tighter radii can be achieved with other alloys or tempers.

RIVETTING / BOLTING :



Use aluminium blind rivet for junction. Fixing work can be done from one direction. Use stainless steel bolt/nut. When panels are connected with junction hole, the equation of $e > 2D$ indicates a suitable relation between the hole diameter (D) and the distance from the hole center to panel end (E) . To ensure sufficient tensile strength of the hole.



Conventional, Off the shelf equipment can be used including ; universal, Vertical and horizontal routing machines.

To avoid pressure marks on the Alubond Surface when chucking the work pieces, wooden or plastic shims should be used.

The most suitable cutters for both aluminum and Alubond are high-speed steel or carbon tipped cutters which have a wide tooth spacing, radius and small grooves and small lip angles. These cutters produce perfect cuts under the following conditions :

High Speed Steel (HSS) Cutters		
Cutting Speed Max	:	3000 m/min
Feed max	:	24 m/min
Carbide tipped (CT) Cutters		
Cutting Speed Max	:	5000 m/min
Feed max	:	30 m/min

The very simple method of routing makes the shaping ability to Alubond one of its major features. The system allows shapes of various kinds and sizes to be formed out of Alubond. A V-shaped groove is formed in the panel allowing it to be bent without the use of a press brake machine.



SHEARING



The shearing of Alubond ACP panels can be easily done using rotary shears or a guillotine. To prevent damage to the panel, the hold down on the shear should be fitted with a shock absorbing rubber pad.

PUNCHING



Punching flat-formed parts from Alubond is performed in the same way as solid aluminium sheet, using the narrowest possible cutting gap and evenly ground tools.


PLANNING & FILLING OF EDGES



When using a jig saw on Alubond, swarf is often left behind on the edges of the sheet, For removing this swarf and finishing off the edges, plane cutting files work best. Files with screen-like perforated roots, or tools with very coarse or rasp-like cut are recommended for filing. Through these perforations the swarf will be removed from the tool surface. The file profile should be from slightly to fully rounded. The proper filing direction is lengthways along the edge. When clamping a sheet of Alubond between jaws, a shim of wood or plastic will protect the surface against damage.

Substructure Systems for Ventilated Facades

Alubond offers state of the art substructure systems for ventilated facades with various cladding options. These systems are developed based on new architectural trends and requirements. Following are the most popular ventilated systems which caught the attention of architects/ consultants across the globe and are appreciated for their aesthetic expression, easy installation, superior thermal insulation and above all economic pricing.



SYSTEM SLIDER



SYSTEM STONE



SYSTEM TACK



SYSTEM BOLT



SYSTEM BOX



SYSTEM CONTINUAL



SYSTEM FIT



SYSTEM GASKET



SYSTEM HIDE



SYSTEM RIVET

CONTACT US

Eurocon Buildings Industries F.Z.C
Mulk Holdings F.Z.C
P.O.Box 42642 Hamriya Free Zone, Sharjah, U.A.E
Tel: 971-6-5262202
Fax: 971-6-5262203
E-mail : info@alubond.com

American Building Technologies Inc.
6957 Olde Creek Road Rockford, Illinois 61114, U.S.A
Tel: 815 331 4121
Fax: 815 713 4525
E-mail : greeninfo@alubond.com

Alubond Europe doo
Nemanjina 130,
26320 Banatski Karlovac, Serbia
Tif : +381 13 652 852
E-mail : info@alubondeurope.com
Website : www.alubond.com

Alubond DACS India (P) Ltd
Enpar House, Ambika Mills Compound
Senpati Bapat Marg, Lower Parel,
Mumbai 400013, India
Tel : +91 22 4321 1400
Fax: +91 22 4321 14444
E-mail : ialubonddacs@alubond.com

Alubond Middle East L.L.C
P.O.Box No. 30103, al Jurf, Ajman, U.A.E
Tel : +971-6-5262202
Fax: 971-6-5262203
E-mail : alubondmiddleeast@alubond.com

Alubond International Egypt for Trading
Villa 412, Abdelmnmem Riyad Street,
Al Motamayez Districe 6th October,
Giza Governate, Cairo, Egypt.
Tel : +20 102 280 0900
E-mail : egypt@alubond.com

Alubond U.S.A
Tel : +1 765 491-2190
E-mail : dlem@alubond.com

Alubond Canada Inc.
3600A Laird Road, Unit #15
Mississauga, ON, L5L 0A3
Tel : +1 800 956 8118
E-mail : canada@alubond.com

www.alubond.com/canada



WES003 - FR-A2
MES059 - FR-B
MES055 - FR-B1
MES056 - FR
CF5001 - FR-B1
CF5002 - FR-B2