

# RIVENDALE

## FIBRE CEMENT SLATES

Cedral Rivendale slates are designed to reflect the qualities of natural slate, at a fraction of the cost. Available in blue black or heather, Rivendale slates have a beautifully textured surface and dressed edges, combining the benefit of modern slate technology with the look of a natural slate. With more cement and fibres than any other, all Cedral slates are the strongest slates in the market. They come with a 20-year colour and 30-year structural guarantee.



A beautifully detailed surface and dressed edge that together reproduce the attractive appearance of natural slate.

Irish made  
for Irish weather

Strongest  
slate

Quality  
guarantees

Guaranteed  
Irish

Sustainable

Design scope

Highest water  
repellency



### Technical data

|                                         |                                                                                                                          |
|-----------------------------------------|--------------------------------------------------------------------------------------------------------------------------|
| Size of slate                           | 600mm x 300mm                                                                                                            |
| Minimum pitch                           | 25° (110mm head lap)                                                                                                     |
| Maximum pitch                           | 90°                                                                                                                      |
| Typical laps                            | 100, 110mm                                                                                                               |
| Maximum gauge                           | 245-250mm                                                                                                                |
| Slate thickness                         | 4mm                                                                                                                      |
| Covering capacity (net)                 | 13.4 slates/m² (100mm lap)<br>13.6 slates/m² (110mm lap)                                                                 |
| Weight of slating (approx.)             | 20.4 kg/m² (0.20 kN/m²) (100mm lap)<br>20.9 kg/m² (0.20 kN/m²) (110mm lap)                                               |
| Battens required                        | 4.00 (net lin.m/m²) (100mm lap)                                                                                          |
| Batten size recommended (fixed to SR82) | 50 x 25mm for rafters/supports not exceeding 400mm centres<br>50 x 35mm for rafters/supports not exceeding 600mm centres |
| Fixings                                 | Slate nails (30 x 2.65mm)<br>Copper disc rivets (19mm dia. x 2mm stem)                                                   |
| Authority                               | EN 492                                                                                                                   |

Cedral Rivendale slates are manufactured to EN492, Type NT, 4.0mm thick Fibre Cement Slates in Ireland, with a nominal average density of 1970 kg/m³ and a minimum apparent density of 1750 kg/m³. Rivendale slates have a textured surface with a dressed edge and are offered with a 20 year manufacturer's colour guarantee due to Cedral's siliconised painting process and a 30 year structural guarantee.

Etex Ireland Ltd. is independently certified as meeting requirements of ISO 9001 (Quality), ISO 14001 (Environment), ISO 45001 (Safety) and BES 6001 (Responsible Sourcing). This information is available for download at [cedral.ie](http://cedral.ie)



Rivendale Blue Black



Rivendale Heather

The printing process restricts the exact representation of colours. For true colour reference, please request product samples.